

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курган (3522)50-90-47
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13

Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саранск (8342)22-96-24
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97

Тверь (4822)63-31-35
Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

akm@nt-rt.ru || <https://ametek.nt-rt.ru/>

TR-2000 Multi-Function Recorder

FOR GENERATION, TRANSMISSION, AND DISTRIBUTION POWER SYSTEM MONITORING
MULTI-FUNCTION RECORDER

For all types of power system events, the TR-2000 Multi-Function Recorder provides all the information you need to capture the complete picture. With the true integrated functionality of the TR-2000, you have one place for all your answers. Simultaneously perform: transient recording, disturbance recording, phasor measurements, power quality analysis, and sequence of events recording. The TR-2000 provides answers when you need them with as much information as you need to get results quick. The system can operate automatically to retrieve events and perform an expert analysis so you have the answers fast, saving time and money. The TR-2000 Multi-Function Recorder takes the place of several devices, integrating their functions into one unit, saving you money on equipment and installation while providing all the answers in one software platform. All of these functions are performed at the highest level so it will meet your needs of today and in the future. In a deregulated environment, the TR-2000 is the best tool to provide the necessary data to increase revenues and retain your customers.

Optimize your power system to improve reliability, shorten your fault clearance times, and verify correct operation of your switchgear and protection equipment. The TR-2000 is ideally suited for your generation, transmission, and distribution power system monitoring.

The TR-2000 can be matched to any application with models available for:

8 Analog / 16, 48, 80, 112 or 144 Digital Inputs
16 Analog / 32, 64, 96, 128 or 160 Digital Inputs
24 Analog / 48, 80 or 112 Digital Inputs
32 Analog / 64, 96 or 128 Digital Inputs



FEATURES AND BENEFITS

- Very high-speed transient recorder—analyze switching transients, lightning strikes
- Transient fault recorder—post fault analysis to verify protection and circuit breaker operations, fault clearance times
- Disturbance recorder/logger—analyze power system stability by recording reclose sequences, power swing, and frequency oscillations
- Trend recording—verify voltage regulation and balancing
- Power quality monitor—voltage and frequency profiles, voltage dips and surges, loss of supply, harmonic content, flicker, voltage and current imbalance
- Phasor Measurement Unit—synchronized phasor measurements, in accordance with IEEE Std C37.118-2005
- Fault locator—calculates distance to fault based on configurable line model
- Real time monitor—view analog, digital inputs, and computed values in near real time
- Sequence of events recorder—1 msec or better resolution on digital contacts



AMETEK

POWER INSTRUMENTS

SPECIFICATIONS

INPUTS

- Number of Channels
 - 8, 16, 24, or 32 Analog
 - 16, 32, 48, 64, 80, 96, 112, 128, 144 or 160 Digital
- Voltage Inputs
 - 63.5 or 110 V RMS nominal
- Current Inputs
 - 1 A or 5 A RMS nominal (thru current shunts/CICT's)
- Frequency Response
 - DC - 1/2 sampling rate
- Accuracy
 - Better than 0.1% of full scale
- Digital Inputs
 - 24/48/125/250 VDC normally open or closed wetted contact

RECORDING (TRANSIENT)

- Recording Resolution
 - 16 bits, 65536 levels (15 plus sign)
- Sample Rate
 - TR-2100 - up to 384 samples per cycle
 - TR-2200 - up to 195 kHz
- Pre-fault Time
 - 2 to 500 cycles
- Post-fault Time
 - Fault length will extend as long as a trigger condition exists. Minimum is 8 to 100 cycles
- Safety Window
 - Number of 'clear' cycles that must occur at the end of the recording: 4 to 16 cycles
- Maximum Record Length
 - Maximum size 1 to 30 sec. (this prevents memory filling with a continuous trigger)

RECORDING (DISTURBANCE)

- Sample Rate
 - 2 x supply frequency (100/120 Hz)
- Pre-fault
 - 10 sec. to 10 min.
- Post-fault Time
 - Fault length will extend as long as a trigger point condition exists. Minimum value is 30 sec. to 5 min.
- Maximum Record
 - Absolute maximum: 30 minutes
- Computed Values
 - Voltage and current, real power, reactive power, apparent power, power factor, total harmonic

distortion and frequency (x2), positive, negative and zero sequence, voltage imbalance

RECORDING (DISTURBANCE LOGGING) - OPTIONAL

- Sample Rate
 - 1/2 x supply frequency (25/30 Hz)
- Recording Time
 - 2 weeks (circulating buffer)

RECORDING (TREND)

- Sampling Interval
 - 1 minute, or 10 minutes - data can be retrieved at up to a 60 minute interval
- Record Length
 - 52 weeks (circulating buffer)
- Stored Parameters
 - Maximum, minimum, and average voltage, current, frequency (2), power, flicker, harmonics, and imbalance. Digital data in SER format at user defined time resolution.

TRIGGERING (TRANSIENT)

- Analog Channels
 - Over/under RMS level, Rate-of-Change and THD. Positive, zero and negative sequence triggers, over, under and R-o-C frequency triggers, differential frequency
- Digital Channels
 - Normal to alarm state and return to normal state. Edge or level sensitive.

TRIGGERING (DISTURBANCE)

- Analog Channels
 - Under/over level of fundamental and R-o-C, frequency and ROCOF, power and frequency oscillation, imbalance and impedance, cross trigger from transient recorder

SYSTEM TIMING

- Time Source
 - Internal GPS receiver with 1 PPS output for phasor measurement
 - Optional IRIG-B
- Accuracy
 - Normally better than +/- 60 ns

Synchronization

- 1 pulse per second on optical port. Any number of systems can be linked together.

COMMUNICATIONS

- Serial Ports
 - Up to 4 x RS232 type
- Default Setting
 - 57.6 kbaud, 8 bits, 1 stop, no parity. Rates can be set up to 115 kbaud.
- Modem
 - Hayes compatible type internal or external, fax compatible
- Phone Line Sharing
 - External unit to share a single phone line with a station phone
- Network
 - 10Base2 (50 ohm coax and BNC), 10baseT, Fiber
 - Network protocol: TCP/IP

DATA STORAGE

- Permanent Storage
 - 40GB Hard Disk
 - 40GB Solid State Drive (optional)

POWER SUPPLY

- Input Voltage Options
 - 100 to 300 VDC, 85 to 264 VAC, (optional 85 to 150 VDC, 85 to 264 VAC)
- Power Requirement
 - 60VA (16 channel), 70VA (32 channel)

VOLTAGE WITHSTAND

Isolation, Impulse Voltage, RFI and ESD per IEEE/IEC Standards

ENCLOSURE

- Cabinet
 - 6U - 8 and 16 channel
 - 8U - 24 and 32 channel
 - 9U - with extended digital channels

ENVIRONMENT

- Operating Temperature
 - 14° to 131°F (-10° to 55°C)
- Relative Humidity
 - 0 to 97% non-condensing

CERTIFICATION

CE

AMETEK

POWER INSTRUMENTS

Алматы (7273)495-231
 Ангартск (3955)60-70-56
 Архангельск (8182)63-90-72
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Благовещенск (4162)22-76-07
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Владикавказ (8672)28-90-48
 Владимир (4922)49-43-18
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Коломна (4966)23-41-49
 Кострома (4942)77-07-48
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курган (3522)50-90-47
 Курск (4712)77-13-04
 Липецк (4742)52-20-81
 Магнитогорск (3519)55-03-13

Россия +7(495)268-04-70

Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Ноябрьск (3496)41-32-12
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Пермь (342)205-81-47
 Петрозаводск (8142)55-98-37
 Псков (8112)59-10-37

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саранск (8342)22-96-24
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Сургут (3462)77-98-35
 Сыктывкар (8212)25-95-17
 Тамбов (4752)50-40-97

Киргизия +996(312)96-26-47

Тверь (4822)63-31-35
 Тольятти (8482)63-91-07
 Томск (3822)98-41-53
 Тула (4872)33-79-87
 Тюмень (3452)66-21-18
 Улан-Удэ (3012)59-97-51
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Чебоксары (8352)28-53-07
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Чита (3022)38-34-83
 Якутск (4112)23-90-97
 Ярославль (4852)69-52-93